



# Mechanical Damage and Combustion of TNT and Composition-B

by Robert J. Lieb, John J. Starkenberg, William Lawrence,  
and Patrick J. Baker

ARL-TR-2554

August 2001

Approved for public release; distribution is unlimited.

20010906 042

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

# Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5069

---

ARL-TR-2554

August 2001

---

## Mechanical Damage and Combustion of TNT and Composition-B

Robert J. Lieb, John J. Starkenberg, William Lawrence,  
and Patrick J. Baker

Weapons and Materials Research Directorate, ARL

---

## Abstract

---

Fracture damage was introduced into trinitrotoluene (TNT) and Composition-B (Comp-B) through uniaxial compression applied at controlled strain rates from 0.1 to 100 s<sup>-1</sup>. The mechanical response was measured with parameters that have been used to characterize the fracture response of gun propellant during its development over the last decade. The damaged high explosive was burned in a small closed bomb in an effort to characterize the fracture surface area that resulted from the uniaxial compression. However, the brittle nature of both the TNT and Comp-B, and the burning character of these materials prevented a completely successful characterization and correlation with the mechanical response. The brittle mechanical response produced wide scatter in the measured parameters, and the apparently erratic burning behavior of the TNT and Comp-B prevented accurate surface area determination from the damaged high explosive. There were some trends that were noted for the mechanical response as a function of strain rate, and an idea of the nature of the fracture damage was attained. However, the roles that fracture play in the violence of the response of high explosive materials to impact and combustion threats remains unclear.

---

## Acknowledgments

---

Michael G. Leadore (ARL, APG, MD) performed all of the mechanical properties tests and conducted all of the closed-bomb firings. His skill and patience with the equipment during this difficult test series is greatly appreciated.

INTENTIONALLY LEFT BLANK.

---

## Contents

---

Acknowledgments	iii
List of Figures	vii
1. Introduction	1
2. Experimental	2
2.1 Mechanical Response Measurements.....	2
2.2 Fracture-Generated Surface Area Measurement .....	4
3. Results	5
3.1 Mechanical Response Measurements.....	5
3.2 Closed-Bomb Firings.....	8
4. Analysis	10
4.1 Mechanical Response.....	10
4.2 Closed-Bomb Firings.....	10
4.3 The Modeling Effort.....	12
5. Conclusions	14
6. References	17
Distribution List	19
Report Documentation Page	37

INTENTIONALLY LEFT BLANK.



---

## List of Figures

---

Figure 1. High-rate servohydraulic tester.....	2
Figure 2. Individual compression curve. ....	3
Figure 3. Characterization parameters. ....	4
Figure 4. Response of Comp-B at $100\text{ s}^{-1}$ .....	5
Figure 5. Average values for TNT and Comp-B. ....	6
Figure 6. Tested specimens of TNT and Comp-B. ....	7
Figure 7. Individual and average burning rate curves. ....	8
Figure 8. Surface area profiles (surface area ratio vs. fraction burned). ....	9
Figure 9. Surface area profile of solid right circular cylindrical specimens.....	12
Figure 10. Plots of damage (right) and material deformation (left) at 50- $\mu\text{s}$ (1%) intervals.....	13

INTENTIONALLY LEFT BLANK.

---

## 1. Introduction

---

The susceptibility to fracture damage of high explosives may play a role in their vulnerability response and in the evolution to violent scenarios. The mechanical response of gun propellant has been correlated with the fracture damage that was suffered under controlled compression of that propellant. This correlation was made with a parameter called the failure modulus that measured the material susceptibility to fracture and a method that successfully determined the fracture generated surface area [1, 2]. This same damage evaluation technique was attempted for the explosive materials trinitrotoluene (TNT) and Composition-B (Comp-B). In this technique, the failure parameter (failure modulus) for the material is measured under specific conditions. Usually the strain rate, temperature, and amount of strain are the parameters that determine the degree of fracture under uniaxial loading conditions. In these experiments, the temperature and amount of strain were held fixed, and the strain rate was varied over four orders of magnitude. The failure modulus was measured, along with other parameters that characterize the response of the material, and then the damaged material was collected and burned within a closed bomb in an effort to determine the correlation between the measured response and the fracture surface area produced.

The technique used to measure the surface area involves establishing the burning rate of the material as a function of pressure using undamaged specimens. Then, damaged material is burned, and using the established burning rates, the exposed surface area can be calculated from the pressure-time curve. Certain assumptions about burning must hold in order to successfully use this procedure. These assumptions will be addressed.

In addition to the experimental analysis previously outlined, a damage model was constructed. The model is a comprehensive theoretical foundation for modeling coupled damage and reaction in energetic materials. Although reaction is not expected, these models may be applicable to the description of material damage produced in the servohydraulic tester used to compress the specimens. The degree of damage (which varies from zero to some value near unity) represents additional surface area that is available to support reaction.

---

## 2. Experimental

---

### 2.1 Mechanical Response Measurements

The mechanical response was measured using a specially designed servohydraulic tester [3] shown schematically in Figure 1. The machine allows compression measurements to be performed at controlled rates as great as  $1000 \text{ s}^{-1}$  for a specimen with a nominal length of 1 cm. Compression is arrested when contact occurs between the impact bell and cone. Therefore, setting the anvil height can accurately predetermine the amount of specimen compression. This contact between bell and cone not only stops the specimen compression, but it also shunts the force around the specimen. The nitrogen spring absorbs the decelerating force of the massive ram and extends its duration. The force applied to the specimen is measured using the quartz piezoelectric gauge inside the impact bell. During compressive response measurements, displacement is measured with a linear variable differential transformer (LVDT) in the actuator column and is corrected for machine stiffness.




Figure 1. High-rate servohydraulic tester.

The specimens were prepared from cast, solid, right-circular cylinders of TNT and Comp-B. The specimen preparation procedure began by cutting the sample with a diamond saw to a length of 1.00 cm. The ends were cut flat, parallel, and perpendicular to the grain axis according to the specifications in a proposed NATO draft Standard Agreement entitled "Uniaxial Compressive Test," which is an updated version of the test published in CPIA Publication 21 [4]. The specimen was then placed on the anvil and tested at 21 °C.

The distance between the anvil and the force gauge when the bell and cone surfaces were mated determines the final strain to which the specimens were taken. That distance was determined by placing a lead specimen on the anvil and performing compression. This allowed any dynamic effects to be taken into account that may have been overlooked in a static measurement. The percentage strain used in these tests was initially selected to be 80%. However, during initial testing, it was observed that initial failure occurred before 10% strain, which showed that all support within the specimen was lost (Figure 2). This indicated that the damage from the initial contact was completed before 10% strain and that any further compression would increase the damage by means of secondary compression of the specimen fragments. This would add to the initial damage and could weaken the correlation between the initial mechanical conditions and the resulting fracture. As a result of this observation, all specimen compression was halted at 10% strain for specimens burned.




Figure 2. Individual compression curve.

The parameters measured in a response characterization test are (1) the modulus, (2) maximum stress, (3) strain at maximum stress, (4) stress at failure, (5) strain at failure, and (6) failure modulus. These parameters and an indication of their origin are illustrated in Figure 3. The first three parameters have the traditional engineering definitions. The failure stress, failure strain, and failure modulus have special values. The failure modulus is the slope of the stress-strain curve in the near linear region between strain at maximum stress, and twice that value. The failure modulus values were established from averaging the values determined from five response curves. The point of failure, from which the stress at failure and strain at failure values were determined, is defined by the intersection of the two lines that determine the modulus and failure modulus. The strain at the intersection of those lines defines the strain at failure; the corresponding stress on the response curve defines the stress at failure. The specimen strain rate for these tests was chosen to be  $0.1 \text{ s}^{-1}$ ,  $1 \text{ s}^{-1}$ ,  $10 \text{ s}^{-1}$ , or  $100 \text{ s}^{-1}$ .




Figure 3. Characterization parameters.

It was hoped that a difference in fracture susceptibility could be established over this range of strain rates.

## 2.2 Fracture-Generated Surface Area Measurement

The shards of the grains that were damaged by uniaxial compression, as previously outlined, were carefully collected and burned in a small-volume (about 25 cc) closed bomb called the dynamic closed bomb (DCB). The bomb was used in an attempt to determine the effect that the mechanical damage had on the rate of pressure generation of the material. In normal propellant burning, the rate of pressurization during combustion is controlled by the intrinsic burning rate of the energetic material and the surface area exposed to the flame. The burning rate or the surface area can be determined from the pressure-time curve if the other is assumed or known. Once the burning rate has been established from undamaged specimens, it is possible to determine the surface area from the combustion pressure-time data.

Undamaged specimens were burned in the DCB at the same loading density that was used in the damaged grain firings. These pressure-time traces were analyzed using the closed-bomb reduction code, BRLCB [5], to establish the burning rates for the TNT and Comp-B used in these tests. Once established, the surface area from all the pressure-time histories can be determined using the same code by selecting the surface area analysis option. The output from the code provides pressure in MPa and the corresponding surface area in square centimeters. This output was converted to intrinsic parameters of fraction burned and surface area ratio ( $S/S_0$ ), respectively, by dividing the pressure by the maximum pressure and the surface area by the initial surface area of the

undamaged grain. This permitted closed bomb runs with different charges, pressures, etc., to be compared. Enough material was damaged to provide two closed bomb firings for each strain rate.

---

### 3. Results

---

#### 3.1 Mechanical Response Measurements

As previously mentioned, a typical compressive stress-strain curve for Comp-B is shown in Figure 2. Secondary compression of the shards of the high explosive specimen is indicated in this figure, and because of this secondary compression, the experiment was stopped at 10% strain. The specimens were then burned in the DCB to determine the surface area caused by the fracture. The initial portion of the uniaxial compressive response of Comp-B at the strain rate of  $100 \text{ s}^{-1}$  is shown in Figure 4.






Figure 4. Response of Comp-B at  $100 \text{ s}^{-1}$ .

These curves were very representative of all the compressive tests that were performed on either material (TNT or Comp-B) at any rate. The response shown in Figure 4 is very brittle, as shown by the dramatic loss of strength after maximum stress. It is also very weak, indicated by the very low values of maximum stress, as compared to curves of conventional energetic materials (gun propellants) that are routinely tested at the U.S. Army Research Laboratory (ARL) [3]. Because the response is severely brittle, there is significant scatter in the maximum stress values, and the curve shapes show significant deviation from each other with some curves (none shown here) displaying double stress

peaks, indicating significant local failure before general brittle failure. Curves such as these indicate very brittle response and great likelihood of material failure in very low-level stress environments. However, attempts were made to characterize the response from these curves by averaging the values for the modulus and failure modulus at each strain rate, which indicate the material resistance to deformation and its fracture susceptibility. These two quantities were calculated for each curve and averaged. These averages and scatter are indicated in Figure 5. The maximum stress, the stress at failure, and the associated strains were not averaged because of the wide scatter in the measured results. From these plots, the indication is that brittle fracture occurs at all strain rates. Figure 6 shows the specimens after uniaxial compression.



(a)




(b)

Figure 5. Average values for TNT and Comp-B.





(a)



(e)



(b)




(f)



(c)



(g)



(d)




(h)

Figure 6. Tested specimens of TNT and Comp-B.


### 3.2 Closed-Bomb Firings

The closed-bomb portion of the experimental procedure posed quite a problem. Previous attempts to characterize the burning of TNT and Comp-B [6, 7] were met with very limited success. Conclusions from these references state that TNT and Comp-B both demonstrate "in-depth" burning. TNT seems to break up during the burning process and spew particles of various sizes into the combustion zone. Comp-B reportedly burns on the surface, as normal gun propellants are assumed to do, but transitions to an in-depth process at some pressure. These burning characteristics do not provide encouragement to analysts using these methods, which have been shown to provide invaluable insight into gun propellant-fracture analysis. However, the attempt to determine the burning rates was made using the procedure outlined in section 1. The results for the individual tests are shown in Figure 7. Note the large differences in slope and magnitude observed for some of the curves, and the fluctuations found in the low-pressure portion of the curves. The average values of these curves (shown on the plots) were used in the surface area analysis of the damaged grains.



TNT

(a)




Comp-B

(b)


Figure 7. Individual and average burning rate curves.

The surface area reductions are shown in Figure 8. The values of  $S/S_0$  at fraction-burned values of zero are extrapolated from the trend as the fraction burned approaches zero. The first value of surface area is calculated for fraction-burned values beginning from 2–3%, based on the assumptions used in BRLCB. This feature of the output program requires an estimate of the initial surface area since the initial area is assumed to be the undamaged area of the specimen with its original dimensions.



TNT

(a)



Comp-B

(b)

Figure 8. Surface area profiles (surface area ratio vs. fraction burned).

---

## 4. Analysis

---

### 4.1 Mechanical Response

The overall mechanical response of the materials is very brittle, as mentioned previously. The brittleness was compounded by the very low strength of the material. Rarely did the failure strength exceed 10 MPa. The failure strain was also very low, not exceeding 5%. However, some minor trends were observed in the response of the specimens.

Comp-B tended to show increased modulus values with increased strain rate, while the failure modulus decreased at increasing strain rate. The exception to this was at the highest strain rate, where the failure modulus becomes less negative (see Figure 5). A greater negative value for the failure modulus indicates a more brittle response. Therefore, this trend of parameters indicates that for Comp-B, as strain rate increases the material becomes more brittle until the strain rate approaches  $100 \text{ s}^{-1}$ . At that point, a slight strengthening occurs that may be reflected in reduced surface area production upon failure. However, the nature of the materials is still very brittle, as is the case whenever the failure modulus has the same magnitude as the modulus. Therefore, any effect of reduced brittleness may be lost in the overall brittle nature of the material. This is especially true considering the scatter observed in the magnitude of the calculated parameters.

TNT showed the same overall brittleness, but demonstrated a different trend. The magnitude of the failure modulus and the modulus seemed to match at each strain rate, i.e., higher modulus values were matched with higher brittleness. This would predict that maximum fracture occurred at maximum stiffness, a trend that indicates a simple relationship. Again, the scatter in the individual measurements is large, so this trend may not be obviously reflected.

These trends were minor and did not affect fracture significantly. In fact, the deduced surface area measurements do not strongly reflect any of these mechanical response observations, as will be discussed.

### 4.2 Closed-Bomb Firings

It should be noted that in order for the burning rates to have good physical meaning, the assumptions made in the analysis program BRLCB must be met. The key assumptions of the data reduction code are the following:

- The igniter material is completely consumed before the energetic materials begin to burn.

- The material begins to burn with all exposed surfaces ignited.
- The mass generation (of gas) is a result of combustion from surface phenomena (no in-depth burning or particle spewing into the flame).

No gun propellant or any other material follows these rules strictly. Deviations from these assumptions include residual igniter material that burns while the energetic material begins to burn, flame spreading, burning irregularities, and mechanical damage. However, the closer the material being burned comes to abiding by these assumptions, the closer the results reflect valid analysis. Some indications that these assumptions were not closely abided in this series include:

- Significant variation in burning rate at low pressure. This indicates that nonuniform, incomplete, or unstable combustion was occurring on the exposed surfaces. (These effects may also be responsible for initial  $S/S_0$  values of less than one.)
- Significant variation in burning rate levels at the same pressure. This indicates that different burning processes may have been occurring at various pressures during combustion (i.e., in-depth combustion or deconsolidation of the surface).
- Different slopes for curves at the same pressure. This may indicate an unstable transition in combustion processes (e.g., going from a process that is primarily surface combustion to another, such as an in-depth process).
- Multiple peaks in the pressure-time plot. Several closed-bomb runs had to be discarded because a low-pressure peak was followed by renewed burning and a second peak, which indicated that the specimens had burned unevenly (e.g., some grains were significantly consumed before others were fully ignited).

While all combustion processes are different and occur in various combinations, the degree of deviation from the assumptions is usually manageably small. With these results, the degree of adherence is difficult to determine without more extensive testing.

The surface area profiles (Figure 8) show additional surface area present in almost all cases. Figure 9 shows the regressive profile of the undamaged specimens. The profile starts at one and gradually decreases as the specimen is consumed. Near the end, it rapidly goes to zero. Although the damaged specimen profiles show additional surface area produced during the burning, the predictions based on mechanical properties are not reflected in the TNT profiles. The lowest and highest strain rates should produce the most surface area (Figure 5b), but the profile suggests that the order jumps from low at low rate to high at the next level, and then produces the same profile at  $10 \text{ s}^{-1}$  and  $100 \text{ s}^{-1}$ . Comp-B profiles (Figure 8) show a similar difference. Mechanical properties indicate a steady increase in surface area with strain rate, with a leveling at the higher rates. The measured profiles show a steady increase up to  $10 \text{ s}^{-1}$ , but then




Figure 9. Surface area profile of solid right circular cylindrical specimens.

the surface area generation is dramatically lowered at  $100 \text{ s}^{-1}$ . This mismatch between mechanical properties prediction and observed results allows reflection on the influence of the irregular burning observations noted earlier.

### 4.3 The Modeling Effort

A comprehensive theoretical foundation for modeling damage, reaction, and the coupling between these two quantities in energetic materials has been developed. Under this formulation, Matheson's tensile distension and damage (TDD) model [8] is used to drive both the viscous-elastic-plastic (VEP) model [9] and an extended version of the multiphase burn (MPB) model of Baer and Nunziato [10]. Although reaction is not expected, these models may be applicable to the description of material damage produced in the servohydraulic tester. It is notable, however, that damage due to shear is not included in TDD. The degree of damage (which varies from zero to some value near unity) represents additional surface area that is available to support reaction.

The models have been implemented in a developmental version of Sandia National Laboratory's CTH software [11], but have not yet been calibrated for application to a wide variety of energetic materials. We have exercised CTH in a simulation of the nonreactive response of a sample in the servohydraulic tester. In order to obtain a significant amount of strain in a short period of time, we chose a strain rate of  $200 \text{ s}^{-1}$ . We ran the simulation for  $250 \mu\text{s}$  to achieve a maximum nominal strain of 5%. The model calibrations that we used were supplied by Sandia with the developmental code, and the response of the associated material may not be representative of that of TNT or Comp-B. In spite of this, the results are informative. Shown in Figure 10 are plots of damage (on the right) and displacement of the material (on the left) at  $50\text{-}\mu\text{s}$  intervals, corresponding to 1% intervals in overall strain. The ram is at the top of the plots and the anvil at the bottom. These show that damage initially appears at the top and, to a lesser extent, bottom of the sample. Through the first  $150 \mu\text{s}$ , damage propagates through the upper quarter of the sample at a moderate pace. During




Figure 10. Plots of damage (right) and material deformation (left) at 50- $\mu$ s (1%) intervals.

the last 100  $\mu$ s, damage propagates at an accelerated pace through the rest of the sample. The highest damage level is found in the region adjacent to the ram and, to a lesser extent, the anvil. Levels of damage in other regions are nearly as high. Regions of low or moderate damage are extremely limited. These predictions reflect the actual damage observed, as shown in Figure 6.

---

## 5. Conclusions

---

The mechanical response of TNT and Comp-B was measured over four decades of strain rate. The response of both high explosive formulations was very brittle and weak, compared to gun propellants measured under similar conditions within ARL. The failure modulus, a measure of the fracture susceptibility, was about the same magnitude as the modulus of the material. In previous measurements, if an energetic material had a failure modulus one-tenth the magnitude of the modulus, the material was considered very brittle and unsuited for use in gun firings. However, the conditions under which gun propellant is used are much different from that of high explosive materials, and the criteria for acceptable use must be independently established. The strength of the high explosive material was also about one tenth of the conventional gun propellants. This implied that the high explosive would fail in a brittle fashion under a relatively low stress environment.

In an attempt to measure the degree by which the fracture damage produced the fracture-generated surface area, a technique was employed that established a correlation between a mechanical failure parameter (the failure modulus) and the amount of surface area generated under uniaxial compression. In this technique, the material damaged under the well-defined uniaxial load was burned in a small closed vessel. The rate of pressurization was analyzed using the closed-bomb code BRLCB and established burning rates for undamaged material, and surface area was extracted. In a successful procedure, a correlation is established between the failure response and the surface area generated.

In this series of tests, the extreme brittleness of the TNT and Comp-B produced mechanical characterization parameters that varied widely under similar test conditions. In addition, burning the high explosive material in the closed vessel proved erratic. The material was difficult to ignite (there were some successful ignitions of the primer without subsequent combustion of the high explosive), and it seemed to burn differently from one experiment to the next under similar ignition conditions. This may be due to deconsolidation during combustion or in-depth burning reported by others, but the effect of the exposed fracture generated surface area on the pressurization was diminished by these burning characteristics.



It was determined, however, that TNT and Comp-B are very brittle and are reduced to rubble after about 5% compression, regardless of the rate of deformation. The actual increase in exposed surface area is unknown, although measured values for increase in initial surface area are over ten times the initial undamaged value. However, it seems as though ignition difficulty would serve to reduce the calculated surface area value, while any deconsolidation during combustion would tend to amplify that value. The difficulty is gauging by how much each process affects the mass generation of the combustion material.

One strongly positive result is the model that was established. It predicted the mechanical behavior of the materials very well and characterized the failure. By examining the shards in Figure 6 and the predicted damage in Figure 10, it is clear that the model shows the extent and type of damage observed in these experiments. The mechanical response has been shown to be very brittle over a wide range of strain rates, and the mechanical properties do not seem to vary widely in this strain rate domain. Further development of this model to incorporate the combustion phase promises to offer additional insights into the behavior of the material under operational and threat conditions.

INTENTIONALLY LEFT BLANK.

---

## 6. References

---

1. Lieb, R. J. "Correlation of the Failure Modulus to Fracture Generated Surface Area in Uniaxially Compressed M30 Gun Propellant." ARL-TR-307, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, November 1993.
2. Lieb, R. J. "Correlation of the Failure Modulus to Fracture Generated Surface Area in Uniaxially Compressed M43 Gun Propellant." ARL-TR-884, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, October 1995.
3. Lieb, R. J. "Mechanical Response and Morphological Characterization of Gun Propellant." ARL-TR-1205, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, September 1996.
4. Hoffman, H. J. (editor). "Uniaxial Compressive Gun Propellant Test." *Solid Propellant Mechanical Behavior Manual*, Section 4.6.4.1, CPIA Publication 21, Johns Hopkins University, Chemical Propulsion Information Agency, Columbia, MD, November 1987.
5. Oberle, W. F., and D. E. Kooker. "BRLCB: A Closed-Chamber Data Analysis Program Part I - Theory and User's Manual." ARL-TR-36, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, January 1993.
6. Velicky, R. W. "The Burning Behavior of TNT in the Closed Bomb." ARLCD-TR-83015, U.S. Army Armament Research and Development Command, Dover, NJ, March 1983.
7. Velicky, R. W. "A Method to Evaluate the Burning Behavior of Secondary Explosives - Composition B." ARLCD-TR-83030, U.S. Army Armament Research and Development Command, Dover, NJ, June 1983.
8. Matheson, E. R. "A Coupled Damage and Reaction Model for Simulating Energetic Materials Response to Impact Hazards." Presented at the JANNAF Workshop on Low-Amplitude Long-Duration Impact and Shock Loading of Energetic Materials, September 1999.
9. Olsen, E. M., J. T. Rosenberg, J. D. Kawamoto, and C. F. Lin. "XDT Investigations by Computational Simulations of Mechanical Response Using a New Viscous Internal Damage Model." Proceedings of the Eleventh International Detonation Symposium, August 1998.

10. Baer, M. R., and J. W. Nunziato. "Compressive Combustion of Granular Materials Induced by Low-Velocity Impact." *Proceedings of the Ninth Symposium on Detonation*, pp. 604-617, August 1989.
11. Hertel, E. S., Jr., R. L. Bell, M. G. Elrick, A. V. Farnsworth, G. I. Kerley, J. M. McGlaun, S. V. Petney, S. A. Silling, P. A. Taylor, and L. Yarrington. "CTH: A Software Family for Multi-Dimensional Shock Physics Analysis." *Proceedings of the 19th International Symposium on Shock Waves*, vol. 1, pp. 377-382, July 1993.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC OCA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	OSD OUSD(A&T)/ODDR&E(R) DR R J TREW 3800 DEFENSE PENTAGON WASHINGTON DC 20301-3800
1	COMMANDING GENERAL US ARMY MATERIEL CMD AMCRDA TF 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN 3925 W BRAKER LN STE 400 AUSTIN TX 78759-5316
1	DARPA SPECIAL PROJECTS OFFICE J CARLINI 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	US MILITARY ACADEMY MATH SCI CTR EXCELLENCE MADN MATH MAJ HUBER THAYER HALL WEST POINT NY 10996-1786
1	DIRECTOR US ARMY RESEARCH LAB AMSRL D DR D SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AI R 2800 POWDER MILL RD ADELPHI MD 20783-1197
3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1197
3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI IS T 2800 POWDER MILL RD ADELPHI MD 20783-1197
	<u>ABERDEEN PROVING GROUND</u>
2	DIR USARL AMSRL CI LP (BLDG 305)

NO. OF  
COPIES ORGANIZATION

1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CP CA  
D SNIDER  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL OP SD TA  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

3 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL OP SD TL  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL CI IS T  
2800 POWDER MILL RD  
ADELPHI MD 20783-1145

1 DIRECTOR  
DA OASARDA  
SARD SO  
103 ARMY PENTAGON  
WASHINGTON DC 20310-0103

1 DPTY ASST SECY FOR R&T  
SARD TT  
THE PENTAGON  
RM 3EA79  
WASHINGTON DC 20301-7100

1 COMMANDER  
US ARMY MATERIEL CMD  
AMXMI INT  
5001 EISENHOWER AVE  
ALEXANDRIA VA 22333-0001

4 COMMANDER  
US ARMY ARDEC  
AMSTA AR CC  
G PAYNE  
J GEHBAUER  
C BAULIEU  
H OPAT  
PICATINNY ARSENAL NJ  
07806-5000

NO. OF  
COPIES ORGANIZATION

2 COMMANDER  
US ARMY ARDEC  
AMSTA AR AE WW  
E BAKER  
J PEARSON  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR TD  
C SPINELLI  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSE  
PICATINNY ARSENAL NJ  
07806-5000

6 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH A  
W ANDREWS  
S MUSALLI  
R CARR  
M LUCIANO  
E LOGSDEN  
T LOUZEIRO  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR CCH P  
J LUTZ  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA AR FSF T  
C LIVECCHIA  
PICATINNY ARSENAL NJ  
07806-5000

1 COMMANDER  
US ARMY ARDEC  
AMSTA ASF  
PICATINNY ARSENAL NJ  
07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER US ARMY ARDEC AMSTA AR QAC T C C PATEL PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC AMSTA AR M D DEMELLA PICATINNY ARSENAL NJ 07806-5000
3	COMMANDER US ARMY ARDEC AMSTA AR FSA A WARNASH B MACHAK M CHIEFA PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC AMSTA AR FSP G M SCHIKSNIS D CARLUCCI PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC AMSTA AR FSP A P KISATSKY PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC AMSTA AR CCH C H CHANIN S CHICO PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC AMSTA AR QAC T D RIGOGLIOSO PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER US ARMY ARDEC AMSTA AR WET T SACHAR BLDG 172 PICATINNY ARSENAL NJ 07806-5000
9	COMMANDER US ARMY ARDEC AMSTA AR CCH B P DONADIA F DONLON P VALENTI C KNUTSON G EUSTICE S PATEL G WAGNECZ R SAYER F CHANG PICATINNY ARSENAL NJ 07806-5000
6	COMMANDER US ARMY ARDEC AMSTA AR CCL F PUZYCKI R MCHUGH D CONWAY E JAROSZEWSKI R SCHLENNER M CLUNE PICATINNY ARSENAL NJ 07806-5000
5	PM SADARM SFAE GCSS SD COL B ELLIS M DEVINE W DEMASSI J PRITCHARD S HROWNAK PICATINNY ARSENAL NJ 07806-5000
1	US ARMY ARDEC INTELLIGENCE SPECIALIST AMSTA AR WEL F M GUERRIERE PICATINNY ARSENAL NJ 07806-5000

NO. OF COPIES	ORGANIZATION
2	PEO FIELD ARTILLERY SYS SFAE FAS PM H GOLDMAN T MCWILLIAMS PICATINNY ARSENAL NJ 07806-5000
12	PM TMAS SFAE GSSC TMA R MORRIS C KIMKER D GUZIEWICZ E KOPACZ R ROESER R DARCY R KOWALSKI R MCDANOLDS L D ULISSE C ROLLER J MCGREEN B PATTTER PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC AMSTA AR WEA J BRESCIA PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC PRODUCTION BASE MODERN ACTY AMSMC PBM K PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY TACOM PM ABRAMS SFAE ASM AB 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM AMSTA SF WARREN MI 48397-5000

NO. OF COPIES	ORGANIZATION
3	COMMANDER US ARMY TACOM PM TACTICAL VEHICLES SFAE TVL SFAE TVM SFAE TVH 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM PM BFVS SFAE ASM BV 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM PM AFAS SFAE ASM AF 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM PM RDT&E SFAE GCSS W AB J GODELL 6501 ELEVEN MILE RD WARREN MI 48397-5000
2	COMMANDER US ARMY TACOM PM SURV SYS SFAE ASM SS T DEAN SFAE GCSS W GSI M D COCHRAN 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	US ARMY CERL R LAMPO 2902 NEWMARK DR CHAMPAIGN IL 61822



<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER US ARMY TACOM PM SURVIVABLE SYSTEMS SFAE GCSS W GSI H M RYZYI 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM PM BFV SFAE GCSS W BV S DAVIS 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER US ARMY TACOM CHIEF ABRAMS TESTING SFAE GCSS W AB QT T KRASKIEWICZ 6501 ELEVEN MILE RD WARREN MI 48397-5000
1	COMMANDER WATERVLIET ARSENAL SMCWV QAE Q B VANINA BLDG 44 WATERVLIET NY 12189-4050
2	TSM ABRAMS ATZK TS S JABURG W MEINSHAUSEN FT KNOX KY 40121
3	ARMOR SCHOOL ATZK TD R BAUEN J BERG A POMEY FT KNOX KY 40121

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
14	COMMANDER US ARMY TACOM AMSTA TR R R MCCLELLAND D THOMAS J BENNETT D HANSEN AMSTA JSK S GOODMAN J FLORENCE K IYER D TEMPLETON A SCHUMACHER AMSTA TR D D OSTBERG L HINOJOSA B RAJU AMSTA CS SF H HUTCHINSON F SCHWARZ WARREN MI 48397-5000
14	BENET LABORATORIES AMSTA AR CCB R FISCELLA M SOJA E KATHE M SCAVULO G SPENCER P WHEELER S KRUPSKI J VASILAKIS G FRIAR R HASENBEIN AMSTA CCB R S SOPOK E HYLAND D CRAYON R DILLON WATERVLIET NY 12189-4050
2	HQ IOC TANK AMMUNITION TEAM AMSIO SMT R CRAWFORD W HARRIS ROCK ISLAND IL 61299-6000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	COMMANDER US ARMY AMCOM AVIATION APPLIED TECH DIR J SCHUCK FT EUSTIS VA 23604-5577
1	DIRECTOR US ARMY AMCOM SFAE AV RAM TV D CALDWELL BLDG 5300 REDSTONE ARSENAL AL 35898
2	US ARMY CORPS OF ENGINEERS CERD C T LIU CEW ET T TAN 20 MASS AVE NW WASHINGTON DC 20314
1	US ARMY COLD REGIONS RSCH & ENGRNG LAB P DUTTA 72 LYME RD HANOVER NH 03755
1	SYSTEM MANAGER ABRAMS ATZK TS LTC J H NUNN BLDG 1002 RM 110 FT KNOX KY 40121
1	USA SBCCOM PM SOLDIER SPT AMSSB PM RSS A J CONNORS KANSAS ST NATICK MA 01760-5057
2	USA SBCCOM MATERIAL SCIENCE TEAM AMSSB RSS J HERBERT M SENNETT KANSAS ST NATICK MA 01760-5057

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	OFC OF NAVAL RESEARCH D SIEGEL CODE 351 J KELLY 800 N QUINCY ST ARLINGTON VA 22217-5660
1	NAVAL SURFACE WARFARE CTR DAHLGREN DIV CODE G06 DAHLGREN VA 22448
1	NAVAL SURFACE WARFARE CTR TECH LIBRARY CODE 323 17320 DAHLGREN RD DAHLGREN VA 22448
1	NAVAL SURFACE WARFARE CTR CRANE DIVISION M JOHNSON CODE 20H4 LOUISVILLE KY 40214-5245
8	DIRECTOR US ARMY NATIONAL GROUND INTELLIGENCE CTR D LEITER M HOLTUS M WOLFE S MINGLEDORF J GASTON W GSTATTENBAUER R WARNER J CRIDER 220 SEVENTH ST NE CHARLOTTESVILLE VA 22091
2	NAVAL SURFACE WARFARE CTR U SORATHIA C WILLIAMS CD 6551 9500 MACARTHUR BLVD WEST BETHESDA MD 20817
2	COMMANDER NAVAL SURFACE WARFARE CTR CARDEROCK DIVISION R PETERSON CODE 2020 M CRITCHFIELD CODE 1730 BETHESDA MD 20084

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
8	US ARMY SBCCOM SOLDIER SYSTEMS CENTER BALLISTICS TEAM J WARD W ZUKAS P CUNNIFF J SONG MARINE CORPS TEAM J MACKIEWICZ BUS AREA ADVOCACY TEAM W HASKELL AMSSB RCP SS W NYKVIST S BEAUDOIN KANSAS ST NATICK MA 01760-5019	2	NAVAL SURFACE WARFARE CTR CARDEROCK DIVISION R CRANE CODE 2802 C WILLIAMS CODE 6553 3A LEGGETT CIR BETHESDA MD 20054-5000
		1	EXPEDITIONARY WARFARE DIV N85 F SHOUP 2000 NAVY PENTAGON WASHINGTON DC 20350-2000
		1	AFRL MLBC 2941 P ST RM 136 WRIGHT PATTERSON AFB OH 45433-7750
9	US ARMY RESEARCH OFC A CROWSON J CHANDRA H EVERETT J PRATER R SINGLETON G ANDERSON D STEPP D KISEROW J CHANG PO BOX 12211 RESEARCH TRIANGLE PARK NC 27709-2211	1	AFRL MLSS R THOMSON 2179 12TH ST RM 122 WRIGHT PATTERSON AFB OH 45433-7718
		2	AFRL F ABRAMS J BROWN BLDG 653 2977 P ST STE 6 WRIGHT PATTERSON AFB OH 45433-7739
8	NAVAL SURFACE WARFARE CTR J FRANCIS CODE G30 D WILSON CODE G32 R D COOPER CODE G32 J FRAYSSE CODE G33 E ROWE CODE G33 T DURAN CODE G33 L DE SIMONE CODE G33 R HUBBARD CODE G33 DAHLGREN VA 22448	1	WATERWAYS EXPERIMENT D SCOTT 3909 HALLS FERRY RD SC C VICKSBURG MS 39180
		5	DIRECTOR LLNL R CHRISTENSEN S DETERESA F MAGNESS M FINGER MS 313 M MURPHY L 282 PO BOX 808 LIVERMORE CA 94550
1	NAVAL SEA SYSTEMS CMD D LIESE 2531 JEFFERSON DAVIS HWY ARLINGTON VA 22242-5160		
1	NAVAL SURFACE WARFARE CTR M LACY CODE B02 17320 DAHLGREN RD DAHLGREN VA 22448	1	AFRL MLS OL L COULTER 7278 4TH ST BLDG 100 BAY D HILL AFB UT 84056-5205

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OSD JOINT CCD TEST FORCE OSD JCCD R WILLIAMS 3909 HALLS FERRY RD VICKSBURG MS 29180-6199
1	DEFENSE NUCLEAR AGENCY INNOVATIVE CONCEPTS DIV 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398
3	DARPA M VANFOSSEN S WAX L CHRISTODOULOU 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
2	SERDP PROGRAM OFC PM P2 C PELLERIN B SMITH 901 N STUART ST STE 303 ARLINGTON VA 22203
1	FAA MIL HDBK 17 CHAIR L ILCEWICZ 1601 LIND AVE SW ANM 115N RESTON VA 98055
1	US DEPT OF ENERGY OFC OF ENVIRONMENTAL MANAGEMENT P RITZCOVAN 19901 GERMANTOWN RD GERMANTOWN MD 20874-1928
1	DIRECTOR LLNL F ADDESSIO MS B216 PO BOX 1633 LOS ALAMOS NM 87545
1	OAK RIDGE NATIONAL LABORATORY R M DAVIS PO BOX 2008 OAK RIDGE TN 37831-6195

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
3	DIRECTOR SANDIA NATIONAL LABS APPLIED MECHANICS DEPT MS 9042 J HANDROCK Y R KAN J LAUFFER PO BOX 969 LIVERMORE CA 94551-0969
1	OAK RIDGE NATIONAL LABORATORY C EBERLE MS 8048 PO BOX 2008 OAK RIDGE TN 37831
1	OAK RIDGE NATIONAL LABORATORY C D WARREN MS 8039 PO BOX 2008 OAK RIDGE TN 37831
5	NIST J DUNKERS M VANLANDINGHAM MS 8621 J CHIN MS 8621 J MARTIN MS 8621 D DUTHINH MS 8611 100 BUREAU DR GAITHERSBURG MD 20899
1	HYDROGEOLOGIC INC SERDP ESTCP SPT OFC S WALSH 1155 HERNDON PKWY STE 900 HERNDON VA 20170
3	NASA LANGLEY RSCH CTR AMSRL VS W ELBER MS 266 F BARTLETT JR MS 266 G FARLEY MS 266 HAMPTON VA 23681-0001
1	NASA LANGLEY RSCH CTR T GATES MS 188E HAMPTON VA 23661-3400
1	FHWA E MUNLEY 6300 GEORGETOWN PIKE MCLEAN VA 22101

NO. OF  
COPIES ORGANIZATION

3 CYTEC FIBERITE  
R DUNNE  
D KOHLI  
R MAYHEW  
1300 REVOLUTION ST  
HAVRE DE GRACE MD 21078

1 USDOT FEDERAL RAILRD  
M FATEH RDV 31  
WASHINGTON DC 20590

1 MARINE CORPS  
INTLLGNC ACTVTY  
D KOSITZKE  
3300 RUSSELL RD STE 250  
QUANTICO VA 22134-5011

1 DIRECTOR  
NATIONAL GRND INTLLGNC CTR  
IANG TMT  
220 SEVENTH ST NE  
CHARLOTTESVILLE VA  
22902-5396

1 SIOUX MFG  
B KRIEL  
PO BOX 400  
FT TOTTEN ND 58335

2 3TEX CORPORATION  
A BOGDANOVICH  
J SINGLETARY  
109 MACKENAN DR  
CARY NC 27511

1 3M CORPORATION  
J SKILDUM  
3M CENTER BLDG 60 IN 01  
ST PAUL MN 55144-1000

1 DIRECTOR  
DEFENSE INTLLGNC AGNCY  
TA 5  
K CRELLING  
WASHINGTON DC 20310

1 ADVANCED GLASS FIBER YARNS  
T COLLINS  
281 SPRING RUN LANE STE A  
DOWNINGTON PA 19335

NO. OF  
COPIES ORGANIZATION

1 COMPOSITE MATERIALS INC  
D SHORTT  
19105 63 AVE NE  
PO BOX 25  
ARLINGTON WA 98223

1 JPS GLASS  
L CARTER  
PO BOX 260  
SLATER RD  
SLATER SC 29683

1 COMPOSITE MATERIALS INC  
R HOLLAND  
11 JEWEL CT  
ORINDA CA 94563

1 COMPOSITE MATERIALS INC  
C RILEY  
14530 S ANSON AVE  
SANTA FE SPRINGS CA 90670

2 SIMULA  
J COLTMAN  
R HUYETT  
10016 S 51ST ST  
PHOENIX AZ 85044

2 PROTECTION MATERIALS INC  
M MILLER  
F CRILLEY  
14000 NW 58 CT  
MIAMI LAKES FL 33014

2 FOSTER MILLER  
M ROYLANCE  
W ZUKAS  
195 BEAR HILL RD  
WALTHAM MA 02354-1196

1 ROM DEVELOPMENT CORP  
R O MEARA  
136 SWINEBURNE ROW  
BRICK MARKET PLACE  
NEWPORT RI 02840

NO. OF  
COPIES ORGANIZATION

2    TEXTRON SYSTEMS  
      T FOLTZ  
      M TREASURE  
      1449 MIDDLESEX ST  
      LOWELL MA 01851

1    O GARA HESS & EISENHARDT  
      M GILLESPIE  
      9113 LESAINTE DR  
      FAIRFIELD OH 45014

2    MILLIKEN RSCH CORP  
      H KUHN  
      M MACLEOD  
      PO BOX 1926  
      SPARTANBURG SC 29303

1    CONNEAUGHT INDUSTRIES INC  
      J SANTOS  
      PO BOX 1425  
      COVENTRY RI 02816

1    BATTELLE NATICK OPNS  
      B HALPIN  
      209 W CENTRAL ST STE 302  
      NATICK MA 01760

1    ARMTEC DEFENSE PRODUCTS  
      S DYER  
      85 901 AVE 53  
      PO BOX 848  
      COACHELLA CA 92236

1    NATIONAL COMPOSITE CENTER  
      T CORDELL  
      2000 COMPOSITE DR  
      KETTERING OH 45420

3    PACIFIC NORTHWEST LAB  
      M SMITH  
      G VAN ARSDALE  
      R SHIPPELL  
      PO BOX 999  
      RICHLAND WA 99352

2    AMOCO PERFORMANCE  
      PRODUCTS  
      M MICHNO JR  
      J BANISAUKAS  
      4500 MCGINNIS FERRY RD  
      ALPHARETTA GA 30202-3944

NO. OF  
COPIES ORGANIZATION

8    ALLIANT TECHSYSTEMS INC  
      C CANDLAND MN11 2830  
      C AAKHUS MN11 2830  
      B SEE MN11 2439  
      N VLAHAKUS MN11 2145  
      R DOHRN MN11 2830  
      S HAGLUND MN11 2439  
      M HISSONG MN11 2830  
      D KAMDAR MN11 2830  
      600 SECOND ST NE  
      HOPKINS MN 55343-8367

1    SAIC  
      M PALMER  
      1410 SPRING HILL RD STE 400  
      MS SH4 5  
      MCLEAN VA 22102

1    SAIC  
      G CHRYSSOMALLIS  
      3800 W 80TH ST STE 1090  
      BLOOMINGTON MN 55431

1    AAI CORPORATION  
      T G STASTNY  
      PO BOX 126  
      HUNT VALLEY MD 21030-0126

1    APPLIED COMPOSITES  
      W GRISCH  
      333 NORTH SIXTH ST  
      ST CHARLES IL 60174

1    CUSTOM ANALYTICAL  
      ENG SYS INC  
      A ALEXANDER  
      13000 TENSOR LANE NE  
      FLINTSTONE MD 21530

3    ALLIANT TECHSYSTEMS INC  
      J CONDON  
      E LYNAM  
      J GERHARD  
      WV01 16 STATE RT 956  
      PO BOX 210  
      ROCKET CENTER WV 26726-0210

1    OFC DEPUTY UNDER SEC DEFNS  
      J THOMPSON  
      1745 JEFFERSON DAVIS HWY  
      CRYSTAL SQ 4 STE 501  
      ARLINGTON VA 22202

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>
1	PROJECTILE TECHNOLOGY INC 515 GILES ST HAVRE DE GRACE MD 21078	5	SIKORSKY AIRCRAFT G JACARUSO T CARSTENSAN B KAY S GARBO MS S330A J ADELMANN 6900 MAIN ST PO BOX 9729 STRATFORD CT 06497-9729
5	AEROJET GEN CORP D PILLASCH T COULTER C FLYNN D RUBAREZUL M GREINER 1100 WEST HOLLYVALE ST AZUSA CA 91702-0296	1	PRATT & WHITNEY C WATSON 400 MAIN ST MS 114 37 EAST HARTFORD CT 06108
3	HEXCEL INC R BOE PO BOX 18748 SALT LAKE CITY UT 84118	1	AEROSPACE CORP G HAWKINS M4 945 2350 E EL SEGUNDO BLVD EL SEGUNDO CA 90245
1	HERCULES INC HERCULES PLAZA WILMINGTON DE 19894	2	CYTEC FIBERITE M LIN W WEB 1440 N KRAEMER BLVD ANAHEIM CA 92806
1	BRIGS COMPANY J BACKOFEN 2668 PETERBOROUGH ST HERNDON VA 22071-2443	1	UDLP G THOMAS PO BOX 58123 SANTA CLARA CA 95052
1	ZERNOW TECHNICAL SERVICES L ZERNOW 425 W BONITA AVE STE 208 SAN DIMAS CA 91773	2	UDLP R BARRETT MAIL DROP M53 V HORVATICH MAIL DROP M53 328 W BROKAW RD SANTA CLARA CA 95052-0359
1	GENERAL DYNAMICS OTS L WHITMORE 10101 NINTH ST NORTH ST PETERSBURG FL 33702	3	UDLP GROUND SYSTEMS DIVISION M PEDRAZZI MAIL DROP N09 A LEE MAIL DROP N11 M MACLEAN MAIL DROP N06 1205 COLEMAN AVE SANTA CLARA CA 95052
3	GENERAL DYNAMICS OTS FLINCHBAUGH DIV E STEINER B STEWART T LYNCH PO BOX 127 RED LION PA 17356	4	UDLP R BRYNSVOLD P JANKE MS 170 4800 EAST RIVER RD MINNEAPOLIS MN 55421-1498
1	GKN AEROSPACE D OLDS 15 STERLING DR WALLINGFORD CT 06492		

NO. OF  
COPIES ORGANIZATION

1 UDLP  
D MARTIN  
PO BOX 359  
SANTA CLARA CA 95052

2 BOEING DFENSE & SPACE GP  
W HAMMOND S 4X55  
J RUSSELL S 4X55  
PO BOX 3707  
SEATTLE WA 98124-2207

2 BOEING ROTORCRAFT  
P MINGURT  
P HANDEL  
800 B PUTNAM BLVD  
WALLINGFORD PA 19086

1 BOEING  
DOUGLAS PRODUCTS DIV  
L J HART SMITH  
3855 LAKEWOOD BLVD  
D800 0019  
LONG BEACH CA 90846-0001

1 LOCKHEED MARTIN  
SKUNK WORKS  
D FORTNEY  
1011 LOCKHEED WAY  
PALMDALE CA 93599-2502

1 LOCKHEED MARTIN  
R FIELDS  
1195 IRWIN CT  
WINTER SPRINGS FL 32708

1 MATERIALS SCIENCES CORP  
G FLANAGAN  
500 OFC CENTER DR STE 250  
FT WASHINGTON PA 19034

1 NORTHRUP GRUMMAN CORP  
ELECTRONIC SENSORS  
& SYSTEMS DIV  
E SCHOCH MS V 16  
1745A W NURSERY RD  
LINTHICUM MD 21090

1 GDLS DIVISION  
D BARTLE  
PO BOX 1901  
WARREN MI 48090

NO. OF  
COPIES ORGANIZATION

2 GDLS  
D REES  
M PASIK  
PO BOX 2074  
WARREN MI 48090-2074

1 GDLS  
MUSKEGON OPERATIONS  
W SOMMERS JR  
76 GETTY ST  
MUSKEGON MI 49442

1 GENERAL DYNAMICS  
AMPHIBIOUS SYS  
SURVIVABILITY LEAD  
G WALKER  
991 ANNAPOLIS WAY  
WOODBIDGE VA 22191

6 INST FOR ADVANCED  
TECH  
H FAIR  
I MCNAB  
P SULLIVAN  
S BLESS  
W REINECKE  
C PERSAD  
3925 W BRAKER LN STE 400  
AUSTIN TX 78759-5316

2 CIVIL ENGR RSCH FOUNDATION  
PRESIDENT  
H BERNSTEIN  
R BELLE  
1015 15TH ST NW STE 600  
WASHINGTON DC 20005

1 ARROW TECH ASSO  
1233 SHELBURNE RD STE D8  
SOUTH BURLINGTON VT  
05403-7700

1 R EICHELBERGER  
CONSULTANT  
409 W CATHERINE ST  
BEL AIR MD 21014-3613



<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	UCLA MANE DEPT ENGR IV H T HAHN LOS ANGELES CA 90024-1597
2	UNIV OF DAYTON RESEARCH INST R Y KIM A K ROY 300 COLLEGE PARK AVE DAYTON OH 45469-0168
1	UMASS LOWELL PLASTICS DEPT N SCHOTT 1 UNIVERSITY AVE LOWELL MA 01854
1	IIT RESEARCH CENTER D ROSE 201 MILL ST ROME NY 13440-6916
1	GA TECH RSCH INST GA INST OF TCHNLGY P FRIEDERICH ATLANTA GA 30392
1	MICHIGAN ST UNIV MSM DEPT R AVERILL 3515 EB EAST LANSING MI 48824-1226
1	UNIV OF WYOMING D ADAMS PO BOX 3295 LARAMIE WY 82071
2	PENN STATE UNIV R MCNITT C BAKIS 212 EARTH ENGR SCIENCES BLDG UNIVERSITY PARK PA 16802
1	PENN STATE UNIV R S ENGEL 245 HAMMOND BLDG UNIVERSITY PARK PA 16801

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	PURDUE UNIV SCHOOL OF AERO & ASTRO C T SUN W LAFAYETTE IN 47907-1282
1	STANFORD UNIV DEPT OF AERONAUTICS & AEROBALLISTICS S TSAI DURANT BLDG STANFORD CA 94305
1	UNIV OF MAIN ADV STR & COMP LAB R LOPEZ ANIDO 5793 AEWB BLDG ORONO ME 04469-5793
1	JOHNS HOPKINS UNIV APPLIED PHYSICS LAB P WIENHOLD 11100 JOHNS HOPKINS RD LAUREL MD 20723-6099
1	UNIV OF DAYTON J M WHITNEY COLLEGE PARK AVE DAYTON OH 45469-0240
5	UNIV OF DELAWARE CTR FOR COMPOSITE MTRLs J GILLESPIE M SANTARE S YARLAGADDA S ADVANI D HEIDER 201 SPENCER LABORATORY NEWARK DE 19716
1	DEPT OF MATERIALS SCIENCE & ENGINEERING UNIVERSITY OF ILLINOIS AT URBANA CHAMPAIGN J ECONOMY 1304 WEST GREEN ST 115B URBANA IL 61801

NO. OF  
COPIES ORGANIZATION

- 1 NORTH CAROLINA STATE UNIV  
CIVIL ENGINEERING DEPT  
W RASDORF  
PO BOX 7908  
RALEIGH NC 27696-7908
- 1 UNIV OF MARYLAND  
DEPT OF AEROSPACE ENGNRNG  
A J VIZZINI  
COLLEGE PARK MD 20742
- 3 UNIV OF TEXAS AT AUSTIN  
CTR FOR ELECTROMECHANICS  
J PRICE  
A WALLS  
J KITZMILLER  
10100 BURNET RD  
AUSTIN TX 78758-4497
- 3 VA POLYTECHNICAL  
INST & STATE UNIV  
DEPT OF ESM  
M W HYER  
K REIFSNIDER  
R JONES  
BLACKSBURG VA 24061-0219
- 1 DREXEL UNIV  
A S D WANG  
32ND & CHESTNUT ST  
PHILADELPHIA PA 19104
- 1 SOUTHWEST RSCH INST  
ENGR & MATL SCIENCES DIV  
J RIEGEL  
6220 CULEBRA RD  
PO DRAWER 28510  
SAN ANTONIO TX 78228-0510

ABERDEEN PROVING GROUND

- 1 US ARMY MATERIEL  
SYSTEMS ANALYSIS ACTIVITY  
P DIETZ  
392 HOPKINS RD  
AMXSY TD  
APG MD 21005-5071
- 1 DIRECTOR  
US ARMY RESEARCH LAB  
AMSRL OP AP L  
APG MD 21005-5066

NO. OF  
COPIES ORGANIZATION

ABERDEEN PROVING GROUND (CONT)

- 91 DIR USARL  
AMSRL CI  
AMSRL CI H  
W STUREK  
AMSRL CI S  
A MARK  
AMSRL CS IO FI  
M ADAMSON  
AMSRL SL BA  
AMSRL SL BL  
D BELY  
R HENRY  
AMSRL SL BG  
AMSRL SL I  
AMSRL WM  
J SMITH  
AMSRL WM B  
A HORST  
AMSRL WM BA  
D LYON  
AMSRL WM BC  
P PLOSTINS  
J NEWILL  
S WILKERSON  
A ZIELINSKI  
AMSRL WM BD  
B FORCH  
R FIFER  
R PESCE RODRIGUEZ  
B RICE  
AMSRL WM BE  
C LEVERITT  
AMSRL WM BF  
J LACETERA  
AMSRL WM BR  
C SHOEMAKER  
J BORNSTEIN  
AMSRL WM M  
D VIECHNICKI  
G HAGNAUER  
J MCCAULEY  
AMSRL WM MA  
L GHIORSE  
S MCKNIGHT  
AMSRL WM MB  
B FINK  
J BENDER  
T BOGETTI  
R BOSSOLI  
L BURTON

NO. OF  
COPIES ORGANIZATION

ABERDEEN PROVING GROUND (CONT)

K BOYD  
S CORNELISON  
P DEHMER  
R DOOLEY  
W DRYSDALE  
G GAZONAS  
S GHIORSE  
D GRANVILLE  
D HOPKINS  
C HOPPEL  
D HENRY  
R KASTE  
M KLUSEWITZ  
M LEADORE  
R LIEB  
E RIGAS  
J SANDS  
D SPAGNUOLO  
W SPURGEON  
J TZENG  
E WETZEL  
A FRYDMAN  
AMRSL WM MC  
J BEATTY  
E CHIN  
J MONTGOMERY  
A WERECZCAK  
J LASALVIA  
J WELLS  
AMRSL WM MD  
W ROY  
S WALSH  
AMRSL WM T  
B BURNS  
M ZOLTOSKI  
AMRSL WM TA  
W GILLICH  
T HAVEL  
J RUNYEON  
M BURKINS  
E HORWATH  
B GOOCH  
W BRUCHEY  
M NORMANDIA

NO. OF  
COPIES ORGANIZATION

ABERDEEN PROVING GROUND (CONT)

AMRSL WM TB  
D KOOKER  
P BAKER  
AMRSL WM TC  
R COATES  
AMRSL WM TD  
A DAS GUPTA  
T HADUCH  
T MOYNIHAN  
F GREGORY  
M RAFTENBERG  
M BOTELER  
T WEERASOORIYA  
D DANDEKAR  
A DIETRICH  
AMRSL WM TE  
A NIILER  
J POWELL  
AMRSL SS SD  
H WALLACE  
AMRSL SS SE DS  
R REYZER  
R ATKINSON

NO. OF  
COPIES ORGANIZATION

- 1 LTD  
R MARTIN  
MERL  
TAMWORTH RD  
HERTFORD SG13 7DG  
UK
- 1 SMC SCOTLAND  
P W LAY  
DERA ROSYTH  
ROSYTH ROYAL DOCKYARD  
DUNFERMLINE FIFE KY 11 2XR  
UK
- 1 CIVIL AVIATION  
ADMINSTRATION  
T GOTTESMAN  
PO BOX 8  
BEN GURION INTERNL AIRPORT  
LOD 70150  
ISRAEL
- 1 AEROSPATIALE  
S ANDRE  
A BTE CC RTE MD132  
316 ROUTE DE BAYONNE  
TOULOUSE 31060  
FRANCE
- 1 DRA FORT HALSTEAD  
P N JONES  
SEVEN OAKS KENT TN 147BP  
UK
- 1 DEFENSE RESEARCH ESTAB  
VALCARTIER  
F LESAGE  
COURCELETTE QUEBEC  
COA IRO  
CANADA
- 1 SWISS FEDERAL ARMAMENTS  
WKS  
W LANZ  
ALLMENDSTRASSE 86  
3602 THUN  
SWITZERLAND
- 1 DYNAMEC RESEARCH AB  
AKE PERSSON  
BOX 201  
SE 151 23 SODERTALJE  
SWEDEN

NO. OF  
COPIES ORGANIZATION

- 1 ISRAEL INST OF  
TECHNOLOGY  
S BODNER  
FACULTY OF MECHANICAL  
ENGR  
HAIFA 3200  
ISRAEL
- 1 DSTO MATERIALS RESEARCH  
LAB  
NAVAL PLATFORM  
VULNERABILITY  
SHIP STRUCTURES & MTRLS DIV  
N BURMAN  
PO BOX 50  
ASCOT VALE VICTORIA  
AUSTRALIA 3032
- 1 ECOLE ROYAL MILITAIRE  
E CELENS  
AVE DE LA RENAISSANCE 30  
1040 BRUXELLE  
BELGIQUE
- 1 DEF RES ESTABLISHMENT  
VALCARTIER  
A DUPUIS  
2459 BOULEVARD PIE XI NORTH  
VALCARTIER QUEBEC  
CANADA  
PO BOX 8800 COURCELETTE  
GOA IRO QUEBEC  
CANADA
- 1 INSTITUT FRANCO ALLEMAND  
DE RECHERCHES DE SAINT  
LOUIS  
DE M GIRAUD  
5 RUE DU GENERAL  
CASSAGNOU  
BOITE POSTALE 34  
F 68301 SAINT LOUIS CEDEX  
FRANCE
- 1 ECOLE POLYTECH  
J MANSON  
DMX LTC  
CH 1015 LAUSANNE  
SWITZERLAND

NO. OF COPIES	ORGANIZATION
1	TNO PRINS MAURITS LABORATORY R IJSSELSTEIN LANGE KLEIWEG 137 PO BOX 45 2280 AA RIJSWIJK THE NETHERLANDS
2	FOA NATL DEFENSE RESEARCH ESTAB DIR DEPT OF WEAPONS & PROTECTION B JANZON R HOLMLIN S 172 90 STOCKHOLM SWEDEN
2	DEFENSE TECH & PROC AGENCY GROUND I CREWTHERR GENERAL HERZOG HAUS 3602 THUN SWITZERLAND
1	MINISTRY OF DEFENCE RAFAEL ARMAMENT DEVELOPMENT AUTH M MAYSELESS PO BOX 2250 HAIFA 31021 ISRAEL
1	TNO DEFENSE RESEARCH I H PASMAN POSTBUS 6006 2600 JA DELFT THE NETHERLANDS
1	B HIRSCH TACHKEMONY ST 6 NETAMUA 42611 ISRAEL
1	DEUTSCHE AEROSPACE AG DYNAMICS SYSTEMS M HELD PO BOX 1340 D 86523 SCHROBENHAUSEN GERMANY

INTENTIONALLY LEFT BLANK.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 2001	3. REPORT TYPE AND DATES COVERED Final, July 1999–October 1999	
4. TITLE AND SUBTITLE Mechanical Damage and Combustion of TNT and Composition-B			5. FUNDING NUMBERS 1L16Z618AH43	
6. AUTHOR(S) Robert J. Lieb, John J. Starkenberg, William Lawrence, and Patrick J. Baker				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-MB Aberdeen Proving Ground, MD 21005-5069			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-2554	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Fracture damage was introduced into trinitrotoluene (TNT) and Composition-B (Comp-B) through uniaxial compression applied at controlled strain rates from 0.1 to 100 s <sup>-1</sup> . The mechanical response was measured with parameters that have been used to characterize the fracture response of gun propellant during its development over the last decade. The damaged high explosive was burned in a small closed bomb in an effort to characterize the fracture surface area that resulted from the uniaxial compression. However, the brittle nature of both the TNT and Comp-B, and the burning character of these materials prevented a completely successful characterization and correlation with the mechanical response. The brittle mechanical response produced wide scatter in the measured parameters, and the apparently erratic burning behavior of the TNT and Comp-B prevented accurate surface area determination from the damaged high explosive. There were some trends that were noted for the mechanical response as a function of strain rate, and an idea of the nature of the fracture damage was attained. However, the roles that fracture play in the violence of the response of high explosive materials to impact and combustion threats remains unclear.				
14. SUBJECT TERMS TNT, Comp-B, closed bomb, burn rate			15. NUMBER OF PAGES 41	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.



## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-2554 (Lieb) Date of Report August 2001
2. Date Report Received \_\_\_\_\_
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_
4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_
5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_
6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
E-mail Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Name

\_\_\_\_\_  
Street or P.O. Box No.

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)  
**(DO NOT STAPLE)**